

Material ref AR145

Black Class 'O'PVC Nitrile Foam

Nitrile rubber based elastomeric foam, soft and flexible closed cell material, low thermal conductivity and excellent flame retardency.

Supplied as a self adhesive backed strip. (material structure does not allow it to be converted to strip form without producing a untidy edge and is not recommended in application where is can be seen and presentation is important. for information on self adhesive please see [material ref, AR990 hot melt double sided adhesive tape data sheet/guidance sheet](#))

Thickness range & strip coil lengths

6mm, 10mm, 12mm, 20mm and 25mm thick -

Available in sheet & strip etc. See test data sheet for further specification details.

Material Guide: Sponge/Foams, Closed Cell

Materials are listed below most economical (to the left) to most expensive (to the right)

Materials	Polyethylene	Nitrile	PVC	EPDM	EPDM	Neoprene
Material Ref	220 (Black) 221 (White)	145	210 (Black) 211 (White)	120	122	110
Polymer Type	Plastic	Plastic/Rubber Blend	Plastic	Rubber	Rubber	Rubber
Colour	Black & White	Black	Black & White	Black	(off) White	Black
Density	33 kgm/mtr3	60/90 kgm/mtr3	100/125 kgm/mtr3	130/170 kgm/mtr3	120/160 kgm/mtr3	150/190 kgm/mtr3
Hardness	49 Shore '00'	No Data (Soft)	20/40 Shore '00'	40/45 Shore '00'	40/45 Shore '00'	43/48 Shore '00'
Temperature Max	+100C°	+85C°	+60C°	+90C°	+90C°	+75C°
Temperature Min	-80C°	-50C°	-30C°	-30C°	-30C°	-40C°
Flame Retardency	None	Class'0'	FMVSS	FMVSS302	FMVSS302	FMVSS302
Compression Set	See data sheet	No Data	30%	<5%	<2%	<5%
Acoustic Data	No Data	Yes See Data Sheet	No Data	No Data	No Data	No Data
Surface	Skin	Skin	Skin	Cell	Cell	Cell

Delivery

95% of products are despatched within 24hours of receiving order (exception: self adhesive solid neoprene strip, 3 to 5 working days). If orders are required by a specific deadline please email or phone prior placing your order for definite delivery date.

Material samples are available by request and specific questions can be asked via email:

sales@rubberonline.co.uk

The above is a rough guide and is subject to change without notice.

This information is designed to guide you, the customer, to the most suitable product for your intended application.

The assessment of use is the responsibility of the customer and any liability will remain with the customer.

Terms and conditions apply.

We are committed to customer satisfaction, if you have any concerns about our products or service please contact on us 01268 732185 and ask for customer services.