

Guidance sheet (please see test data sheet for further information)

## Material ref AR410

# Black Natural Shotblast 50° Shore

An excellent high quality abrasion resistant rubber material, Good resistant to dilute acids and alkalis. Applications include chute linings, conveyor skirts also general gasketing and sealing and often used as Replaceable port seal rubber

Can be used in a range of applications including gasketing & sealing.

### Thickness range & strip coil lengths

6mm thick - supplied in strip form 10mtrs long

(10mtr packs – 1 coil x 10mtrs, 50mtr packs – 5 coils x 10mtrs each).

8mm, 10mm, 12mm, 15mm thick - supplied in strip form 5mtrs long

(10mtr packs – 2 coils x 5mtr each & 50mtr packs – 10 coils x 5mtrs each).

Available in sheet, strip & washers etc,

See test data sheet for further specification.



### Delivery

95% of products are despatched within 24hours of receiving order (exception: self adhesive solid neoprene strip, 3 to 5 working days). If orders are required by a specific deadline please email or phone prior placing your order for definite delivery date.

Material samples are available by request and specific questions can be asked via email:

[sales@rubberonlinelimited.co.uk](mailto:sales@rubberonlinelimited.co.uk)

The above is a rough guide and is subject to change without notice.

This information is designed to guide you, the customer, to the most suitable product for your intended application.

The assessment of use is the responsibility of the customer and any liability will remain with the customer.

Terms and conditions apply.

We are committed to customer satisfaction, if you have any concerns about our products or service please contact on us 01268 732185 and ask for customer services.