

Guidance sheet (please see test data sheet for further information)

Material ref AR490

Anti Vibration Cork/Nitrile Rubber

Product Description

Low compression medium density cork and rubber material for noise and vibration control with excellent oil resistance.

Applications

Vibration control in technical equipment rooms, vibration isolation for machinery, IE: compressors pumps, presses, looms & motors, runways, rail & subway isolation pads, building acoustic suspension elements & system for walls, ceilings pipings etc

Strip length, width & thickness range

Supplied in metre long strips, 50mm, 100mm, 150mm & 200mm wide
In thicknesses 6mm, 10mm, 13mm 20mm & 25mm thick



Delivery

95% of products are despatched within 24hours of receiving order (exception: self adhesive solid neoprene strip, 3 to 5 working days). If orders are required by a specific deadline please email or phone prior placing your order for definite delivery date.

Material samples are available by request and specific questions can be asked via email:

sales@rubberonlinelimited.co.uk

The above is a rough guide and is subject to change without notice.

This information is designed to guide you, the customer, to the most suitable product for your intended application.

The assessment of use is the responsibility of the customer and any liability will remain with the customer.

Terms and conditions apply.

We are committed to customer satisfaction, if you have any concerns about our products or service please contact on us 01268 732185 and ask for customer services.