

Guidance sheet (please see test data sheet for further information)

Material ref AR501 Nitrile Bonded Cork

An excellent general purpose gasketing material, its toughness and good compressibility characteristics make it highly satisfactory in a very wide range of applications.

The material has a very low swelling in oils and fuels, which makes it especially suitable for transformer applications

Can be used in a range of applications including gasketing & sealing.

Thickness range & strip coil lengths

(not all thicknesses available in all products)

1.5mm, 3mm thick - supplied in strip form 10mtrs long

(10mtr packs – 1 coil x 10mtrs, 50mtr packs – 5 coils x 10mtrs each).

Available in sheet & strip.

See test data sheet for further specification.



Delivery

95% of products are despatched within 24hours of receiving order (exception: self adhesive solid neoprene strip, 3 to 5 working days). If orders are required by a specific deadline please email or phone prior placing your order for definite delivery date.

Material samples are available by request and specific questions can be asked via email:

sales@rubberonlinelimited.co.uk

The above is a rough guide and is subject to change without notice.

This information is designed to guide you, the customer, to the most suitable product for your intended application.

The assessment of use is the responsibility of the customer and any liability will remain with the customer.

Terms and conditions apply.

We are committed to customer satisfaction, if you have any concerns about our products or service please contact on us 01268 732185 and ask for customer services.