

Material ref AR992

Reinforced Transfer Adhesive Tape

PET Square Scrim

Material Reference- 992
Colour (silicone release paper)- Yellow/Orange
Issue Date- March 2011

Properties	Unit	Value
Thickness, adhesive + carrier	mm	0.09
Thickness, adhesive only	mm	0.065
180 degree peel adhesion, open side	N/m	1500
180 degree peel adhesion, closed side	N/m	1500
Polyester loop tack, open side	N/m	1600
Polyester loop tack, closed side	N/m	1600
Release from self	N/m	10
Serviceable temperature	C°	-15 to +120
Recommended application temperature	C°	+5 to +25
Shear adhesion 1kg @23 deg C	>48	Hours
Shelf Life	12	Months

Other information

A double sided transfer adhesive tape on scrim carrier.

Supplied only applied to material ref: 010, Black Magnetic Rubber Strip
272, Open Cell, Class '0' Acoustic Foam Sheet

Data has been copied from manufactures/distributors data test sheet and is intended to be used for guidance and come without warranty or guarantee.

As individual operating conditions influence the application of each product, the information supplied in this datasheet can only be seen as a rough guideline

It is the responsibility of you, the customer to assess the suitability of product supplied for the purpose for which they are to be used.

Datasheet is subject to alteration without prior notice. This Data Sheet supersedes all previous data sheets, Rubberonline Terms and conditions apply

(Source ref: 16-01-12)